


excalibur

COMPACT CLASS



CATRON
*theimeg*TM

Industrial Radio Remote Controls

excalibur

COMPACT CLASS

The compact **excalibur** is the entry model into the Cattron-Theimeg ct24-class. Hard to believe that this device weighing only 300 grams can move loads weighing tons on cranes and grabbers almost as if they were toys. The **excalibur** is not only very small; it also has state-of-the-art-technology. It sets new standards in terms of handling, operating safety and flexibility. And all that at a price which is really excellent value for money.

Hardly any other system of this size offers such a wide range of functions and capabilities. Two transmitter housing sizes are available: With 6 or 8 and 10 or 12 pushbuttons with excellent tactile feedback and an extremely long working life of more than 1 million switching cycles. The range of applications therefore covers everything from light overhead gantry cranes via tower cranes through to dual-hoist cranes or grabbers.

Thanks to the one-piece elastic mat with integrated push-buttons the **excalibur** also defies winds, weather and adverse conditions. It even operates at winter temperatures down to -20° . An integrated pressure element avoids condensation inside the housing, caused by temperature changes.

- Sets standards in terms of ergonomics, operational safety and flexibility
- Can be used worldwide thanks to its versatile configuration options
- Applications from simple hoists, machine control or gate control through to large overhead travelling cranes with 2 trolleys and/or additional functions such as a grabber, a magnet etc.
- For tandem and dual-transmitter operation (request & release)

The system is rounded off by a sophisticated safety and servicing concept. The basis of this new innovative concept forms a newly developed electronic key, **TransKey**, which is based on RFID technology. Only with this key you can put the **excalibur** into use and control the associated crane. The chip in the **TransKey** also allows individual configuration of the software to exactly match your requirements.





MAIN FEATURES

Frequency ranges:	402 – 470 MHz (Europe, Asia)
	869 MHz (Europe)
	915 MHz (USA)

Transmitter output:	< 10 mW
---------------------	---------

Electronics

Digital electronics:	Dual-processor technology
System addresses:	24 bits = 16 million addresses
Energy-saving mode:	Automatic shutdown (0 - 30 min)
Power supply:	Quick-replacement battery, NiMH, 3.6 V / 1600 mAh Battery life > 12 h with 100% uninterrupted use

Directives and Standards

IP protection category:	IP 65
Safety class:	EN 954-1 Category 3

Physical Data

Weight:	approx. 290 g (6/8 pushbutton versions)
	approx. 350 g (10/12 pushbutton versions)
Dimensions:	180 x 64 x 39 mm
	(L x W x H, 6/8 pushbutton versions)
	235 x 64 x 39 mm
	(L x W x H, 10/12 pushbutton versions)
Operating temperature:	-20° to +60° C

ct24 RECEIVER

The newly developed **ct24** receiver range is the ideal complement for the **excalibur**. It is based on the same pioneering technology and it also has a dual-processor and *TransKey*. The **ct24** series, however, is not only compatible with the **excalibur**. The receivers are thus independent and open for new innovations.

The technology is impressive: Depending on the number of output commands the **excalibur** can be used in combination with 3 different **ct24** receivers; 9, 12 or 17 output relays are available. Regardless of whether the task is simple or extremely complex it thus provides a solution for all possible applications.

The standard version of the receiver housing features two cable glands. If required each receiver can also be supplied with Harting Han24, Han32 or Han64 connectors.

Further details can be found in the relevant data sheet.



USA

Cattron-Theimeg International Inc.
58 West Shenango Street
US Sharpville, Pennsylvania 16150
Phone: +1-724-962-3571
Fax: +1-724-962-4310
mail@cattron-theimeg.com

SOUTH-AFRICA

Cattron-Theimeg Africa (Pty.) Ltd.
24 O'Reilly Merry Road
ZA 1518 Rynfield
Benoni, Gauteng
Phone: +27-11-425-1123
Fax: +27-11-849-5717
cattron@cattronsa.com

CANADA

Cattron-Theimeg Canada Ltd.
150 Armstrong Avenue, Units 5 - 6
CA Georgetown, Ontario L7G 5G8
Phone: +1-905-873-9440
Fax: +1-905-873-9449
salescdn@cattron-theimeg.com

BRAZIL

Cattron-Theimeg Américas Ltda.
Rua Antonio Rodrigues de Carvalho 435
BR Campinas
SP CEP 13033-220
Phone: +55-19-3243-7803
Fax: +55-19-3243-9258
cattronamericas@cattron-theimeg.com

EUROPE

Cattron-Theimeg Europe GmbH & Co. KG
Krefelder Straße 423 - 425
DE 41066 Mönchengladbach
Phone: +49-2161-6363-0
Fax: +49-2161-6363-100
info@theimeg.de

GREAT BRITAIN

Cattron-Theimeg UK Ltd.
Riverdene Industrial Estate, Molesey Road
GB Hersham
Surrey KT12 4RY
Phone: +44-1932-247511
Fax: +44-1932-220937
sales@cattronuk.com