

excalibur

CATTRON CONTROL[®]

Handheld radio remote control transmitter in an innovative, ergonomic housing with advanced dual-processor technology for increased safety. Globally deployable for cranes, lifting equipment and machines.

- High safety-class through redundant hardware and software architecture
- Approvals and frequencies for worldwide deployment
- System configuration via external TransKey
- Customized layout
- 10 or 12 2-step push buttons
- Compatible with multiple receivers
- Compact, ergonomic design



10/12
push buttons

compatible with receiver	ct24	MMCU-4	CCM-12
	✓	✓	✓

CATTRON[™]
a unit of Laird Technologies

Industrial Radio Remote Controls

- Approvals and frequencies for many countries
- Sophisticated and proven safety concept for complying with EN ISO 13849-1
- Customer-specific programming possible
- Can be matched with different receivers
- Tandem and dual-transmitter operation available
- One-piece elastic mat with integrated pushbuttons and shock protection
- Impact-resistant plastic housing

TECHNICAL DATA AND SPECIFICATIONS

RF

Frequency range/power	335 MHz (< 1 mW ERP)
	418, 433, 447 MHz (< 10 mW ERP)
	869 MHz (< 5 mW ERP)
	915 MHz (FCC part 15)
Transmission speed	4.8 to 20 kbit/s
Transmission power	< 10 mW (within the permitted limits)
Receiver sensitivity	-107 dBm
Modulation	FM
RF channel spacing	12.5 kHz; 25 kHz and others
Antenna	internal

Electronics

Digital circuitry	dual-processor technology
System addresses	24 bits = 16 million addresses
Power safe mode	automatic shutdown (configurable: 0–30 minutes)
Power supply	rechargeable battery, NiMH, 3.6 V / 1500 mAh
Autonomy	> 12 h at 100% uninterrupted use

Applied Standards

IP protection class	IP 65
Safety standards	EN ISO 13849-1 Performance Level d EN ISO 13849-2

Mechanical Data

Weight	approx. 350 g
Dimensions	235 x 64 x 39 mm (L x W x H)
Housing	SB plastic, standard colour silver/red, integrated fall protection
Operating temperature	-20° to +60° C

Operation and Indication

Control elements ct24-ET/10	10 push buttons (2-step)
Control elements ct24-ET/12	12 push buttons (2-step)
TransKey	system configuration, address and RF channel
Indication	5 Multi-LED, status, low voltage
Acoustic indication	low voltage indication

Accessories

Batteries	2 x rechargeable batteries, NiMH 3.6 V / 1500 mAh
Battery charger	processor-controlled charger incl. adapter cradle, changing system on the primary side for international use
Labelling	Self-adhesive marking labels

USA

Cattron-Theimeg International Inc.
58 West Shenango Street
US Sharpsville, Pennsylvania 16150
Phone: +1-724-962-3571
Fax: +1-724-962-4310
mail@cattron-theimeg.com

SOUTH-AFRICA

Cattron-Theimeg Africa (Pty.) Ltd.
24 O'Reilly Merry Road
ZA 1518 Rynfield
Benoni, Gauteng
Phone: +27-11-425-1123
Fax: +27-11-849-5717
cattron@cattronsa.com

CANADA

Cattron-Theimeg Canada Ltd.
150 Armstrong Avenue, Units 5 - 6
CA Georgetown, Ontario L7G 5G8
Phone: +1-905-873-9440
Fax: +1-905-873-9449
salescdn@cattron-theimeg.com

BRAZIL

Cattron-Theimeg Américas Ltda.
Rua Antonio Rodrigues de Carvalho 435
BR Campinas
SP CEP 13033-220
Phone: +55-19-3243-7803
Fax: +55-19-3243-9258
cattronamericas@cattron-theimeg.com

EUROPE

Cattron-Theimeg Europe GmbH & Co. KG
Krefelder Straße 423-425
DE 41066 Mönchengladbach
Phone: +49-2161-6363-0
Fax: +49-2161-6363-100
info@theimeg.de

GREAT BRITAIN

Cattron-Theimeg UK Ltd.
Riverdene Industrial Estate, Molesey Road
GB Herisham
Surrey KT12 4RY
Phone: +44-1932-247511
Fax: +44-1932-220937
sales@cattronuk.com